

LINX WOOD CARE

Introduction: Alkyd resin based, decorative wood protector of high spreading capacity.

Characteristics: is an excellent protector against mold fungi that damage and color of wood. Penetrates deeply into the wood thanks to its covering capacity. Thanks to UV-resistant and high quality transparent pigments it contains, Linx Wood Care doesn't whiten and cover natural view of the wood. Along with increasing resistance of the wood, it creates bonding layer for lacquer and paint to be applied. It has moisture-regulating and excellent absorption feature during quick drying-out time.

Instruction for use: Linx Wood Care is decorative protector that you can confidently use on old or new, interior or exterior wood surfaces. It is used on in wood houses, windows, balconies, interior and exterior doors, wood fences, wood stairs, wood ceilings, lambir, wood columns and pillars, furniture accessories and on similar wood surfaces. It should not be applied in bee boxes used in beekeeping, wood surfaces in saunas and wooden containers for unpackaged foods. Moreover, Linx Wood Care should not be used on surfaces made from teak, iroko and other trees that contain excess amount of natural oil. "LINX Wood Care and Colourant" is ready for use. Mix well before and during use. Thinning is not needed.

Dry-out time: 8-10 hours. (20°C 65% relative humidity).

Storage: It should be stored in sealed containers at 5-35°C temperature, in non-humid place that is free from direct sunlight. Storage period: 3 years.

Safety measures: R10: Is inflammable. R66: May cause skin dryness and cracks during repeated exposures. R67: Vapors may cause lethargy and dizziness. S2: Keep out of the reach of children. S3/7/9: Store the package sealed in a cool and well-aired place. S16: Keep the paint away from potential fire sources. Smoking nearby is strictly prohibited. S23: Do not inhale. S24/25: Avoid eye and skin contact. S26: After eye contact wash immediately with plenty of water. S29: Do not dispose to sewerage. S46: Immediately go to the doctor when ingested and submit the package or label. S51: It should be used in well-aired places.

- Owns AZS-034-98 Standard
- Owns ISO 9001:2008 document

Panda Boya: Binagadi Highway, 4th Madan str.276/1

Tel: (+994 12) 401 90 00, Fax: (+994 12) 401 90 01