

Panda Super Mat Boya (Matt Paint)

Introduction: Alkyd-based final coat matt paint.

Characteristics: High covering ability, non-yellowing , stiff and resistant to atmospheric effects.

Instructions for use: It is used for painting any surface in interior and exterior works. Shake well prior to opening lid of the paint and mix after opening. When brush is used 1 liter is thinned with 50-100 ml "Panda Sintetik Tiner" (Synthetic Thinner) and when sprayer is used 1 liter is thinned with 100-150 ml Panda Sintetik Tiner.

Dry-out time: 7-8 hours. Until solid film: 24 hours (20°C)

Storage: The paint should be stored in closed containers between 5-35°C temperatures away from direct sunlight in a non-humid place. Storage period: 3 years.

Consumption: 10-12 m²/lt.

Safety measures: R10: Is inflammable. R66: May cause skin dryness and cracks during repeated exposures. R67: Vapors may cause lethargy and dizziness. S2: Keep out of the reach of children. S3/7/9: Store the package closed in a cool and well-aired place. S16: Keep the paint away from potential fire sources. Smoking nearby is strictly prohibited. S23: Do not inhale. S24/25: Avoid eye and skin contact. S26: After eye contact wash immediately with plenty of water. S29: Do not dispose to sewerage. S46: Immediately go to the doctor when ingested and submit the package or label. S51: It should be used in well-aired places.

- Owns AZS-034-98 Standard
- Owns ISO 9001:2008 document

Panda Boya: Binagadi Highway, 4th Madan str.276/1

Tel: (+994 12) 401 90 00, Fax: (+994 12) 401 90 01