

### **Panda Sellülozik Astar (Cellulosic Primer)**

**Introduction:** Nitrocellulose-based quick-drying primer for wooden and metallic materials.

**Characteristics:** Cellulosic Primer is used in furniture and decorative works for interior use and as frame and covering on any wooden surface before applying final coat paint. The primer has high filling and covering power and is easily rasped and quick drying.

**Instructions for use:** Applied surfaces should be dry, clean and free from dust and oil. Should be thinned with cellulosic thinner and applied with pistol in the form of 2-3 coats. There should be 30-40 minutes interval between coats. After approximately 16 hours final coat paint may be applied.

**Dry-out time:** Touch-dry: 35-45 minutes. Rasping period: minimum 4 hours. (23°C, 50% relative humidity)

**Consumption:** 8-10 m<sup>2</sup>/L on a single coat subject to pores of the surface.

**Storage:** Should be stored in closed containers between 5-35°C temperatures away from direct sunlight in a non-humid place.

**Safety measures:** R10: Is inflammable. R66: May cause skin dryness and cracks during repeated exposures. R67: Vapors may cause lethargy and dizziness. S2: Keep out of the reach of children. S3/7/9: Store the package closed in a cool and well-aired place. S16: Keep the paint away from potential fire sources. Smoking nearby is strictly prohibited. S23: Do not inhale. S24/25: Avoid eye and skin contact. S26: After eye contact wash immediately with plenty of water. S29: Do not dispose to sewerage. S46: Immediately go to the doctor when ingested and submit the package or label. S51: It should be used in well-aired places.

- Owns AZS-034-98 Standard
- Owns ISO 9001:2008 document

**Panda Boya:** Binagadi Highway, 4<sup>th</sup> Madan str.276/1

Tel: (+994 12) 401 90 00, Fax: (+994 12) 401 90 01