



RIMSAN Antirust Paint

Description: Alkyd based anticorrosive primer

Specifications: Used as anti-corrosive primer on all metal surfaces in interior and exterior places. Prepares a sound basis for synthetic paints to be applied on. Metal primer with good levels of adhesion and coverage

Technical details:

Solid content,%(by weight) : 76-78

Density (g/cm³ ,20 °C) : 1.50-1.60

Viscosity (KU,25°C) : 120+5

Flash Point: > 38 °C

Application: Surfaces must be cleaned and sanded from dirt, rust and old paint bubbles. Two coats are applied with one-day break between coats. Can be thinned by 10-15% with Panda SENTETIK TINER. Use between +5°C and +30°C for brush, roller or spray applications. Clean the tools you use with Panda Sentetik Tiner immediately after application.

DRYING TIME: Touch dry in 2-3 hours, dust-free dry in 5-6 hours, hard dry in 12-15 hours.

COVERAGE AREA: 15 m² /L in one coat

SHELF LIFE: Can be stored unopened in cool, dry, frost and sunlight-free conditions. When remains, in order to keep it safely, thinner should be added until the paint is completely covered, or the container should be closed tightly and turned 180 ° once or twice.

SAFETY PRECAUTIONS: R10 : Flammable. R20/21/22: Harmful in contact with skin and if inhaled or swallowed.

S2: Keep out of reach of children. S16: Keep away from sources of ignition. NO SMOKING S24/25: Avoid contact with eyes and skin. S46: If swallowed consult a doctor immediately; show the container or the label; S51: Use only in well-ventilated areas.

- Certified with AZS-034-98
- Certified with ISO 9001:2008

Panda Boya: Binagadi Highway, 4th Madan str.276/1

Tel:(+994 12) 401 90 00, Fax:(+994 12) 401 90 01