

RIMSAN Hammerton Boya (Paint)

Introduction: Styrene-alkyd based, hammered metal looking, air dry last coat hammerton paint.

Characteristics: Easily covers defects and unevenness that cannot be removed when processing metal surfaces. It gives decorative appearance to the surface. The paint is glued well even on irregular surface. Its moisture resistance is high and brightness is long-lasting. The paint is quick-dry.

Instructions for use: Hammerton is utilized when painting any metal items, equipment, spare parts, electrical bars, accessories, machine and devise, elevators, metallic doors and gates. The paint is ready for use. No addition is needed. The surface to be painted should be dry and clean. There should be no dust and wind in the place of painting. Painting should be conducted with spray method. It is recommended to apply pain coats of the same thickness. For achieving an ideal view spraying from 30 cm distance with 2-3 atmospheric pressure should be carried out. Hammerton should be mixed well prior to utilization.

Dry-out time: 2 hours. Complete dry-out: 24 hours (20°C)

Storage: The paint should be stored in closed containers between 5-35°C temperatures away from direct sunlight in a non-humid place. Storage period: 3 years.

Safety measures: R10: Is inflammable. S2: Keep out of the reach of children. S3/7/9: Store the package closed in a cool and well-aired place. S16: Keep the paint away from potential fire sources. Smoking nearby is strictly prohibited. S24/25: Avoid eye and skin contact. S26: After eye contact wash immediately with plenty of water. S29: Do not dispose to sewerage. S46: Immediately go to the doctor when ingested and submit the package or label. S51: It should be used in well-aired places.

- Owns AZS-034-98 Standard
- Owns ISO 9001:2008 document

Panda Boya: Binagadi Highway, 4th Madan str.276/1

Tel: (+994 12) 401 90 00, Fax: (+994 12) 401 90 01