

### **RIMSAN Parke Cam Cila (Parquet Varnish)**

**Introduction:** Single component urethane-alkyd, water-resistant parquet varnish.

**Characteristics:** Resistant to physical and chemical actions, covering and stiff, water-resistant.

**Instructions for use:** Should be mixed well before use.

Dry-out period: 2-3 hours. Complete dry-out: 24 hours (20°C)

**Consumption:** 17 m<sup>2</sup>/lt

**Storage:** Storage period: 3 years.

**Safety measures:** R10: Is inflammable. R66: May cause skin dryness and cracks during repeated exposures. R67: Vapors may cause lethargy and dizziness. S2: Keep out of the reach of children. S3/7/9: Store the package closed in a cool and well-aired place. S16: Keep the paint away from potential fire sources. Smoking nearby is strictly prohibited. S23: Do not inhale. S24/25: Avoid eye and skin contact. S26: After eye contact wash immediately with plenty of water. S29: Do not dispose to sewerage. S46: Immediately go to the doctor when ingested and submit the package or label. S51: It should be used in well-aired places.

- Owns AZS-034-98 Standard
- Owns ISO 9001:2008 document

**Panda Boya:** Binagadi Highway, 4<sup>th</sup> Madan str.276/1

Tel: (+994 12) 401 90 00, Fax: (+994 12) 401 90 01