

RIMSAN RIMSilan

Introduction: Acrylic-based, water-thinned, silicone, matt facade paint.

Characteristics: RIMSILAN paint is resistant against water and atmospheric effects, decorative exterior surface paint that doesn't crack and is highly adherent on any surface, doesn't leave traces of brush and paint roller, doesn't leak when applied. In addition to being ultra-high opacity matt it also ensures removal of moisture on thanks to its air-penetrable feature. The paint prevents blistering and peeling of the surface thanks to the silicone it contains.

Technical characteristics:

Color: See color catalogue.

Brightness: Mat

Dissolved matter, (mass) : 69-70%

Particular weight (g/cm³, 20°C): 1.66-1.67

Viscosity (KU, 25°C): 119-121

pH (25°C): 8.0-9.0

Instructions for use: Item on which the paint is to be applied should be cleaned from other items and old paint. When the surface is properly prepared for last coat painting: the paint will adhere stronger, be smooth and perfect, dry equally and last longer. Firstly cracks are filled with "RIMSAN Akriklik Macun". 2-3 hours after priming with "RIMastar" or "RIMBINDER", the paint is thinned with 15% water and applied twice using paint roller, brush or sprayer with at least an hour interruption. Temperature of the surface and environment should be between 5-30°C while applying.

Dry-out period: dries between 1-3 hours. The second coat is applied after 3 hours. Complete dry-out: 24 hours.

Consumption: 11-13 m²/lt for single coat subject to absorption capacity of the surface.

Storage period: May be stored closed in its original container away from direct sunlight for 2 years, provided that freezing is avoided. For more information please refer to Technical Support Section.

Safety Measures: Avoid eye contact and ingestion. Keep out of the reach of children

Packing information: 2.5lt, 7.5 lt, 15 lt

- Owns AZS-034-98 Standard
- Owns ISO 9001:2008 document

Panda Boya: Binagadi Highway, 4th Madan str.276/1

Tel: (+994 12) 401 90 00, Fax: (+994 12) 448 16 19