

LINX SELLÜLOZİK ASTAR (Cellulosic Primer)

Introduction: Nitrocellulose-based quick-drying primer for wooden, mdf and metallic materials.

Characteristics: Primer is used as frame and covering in furniture, decorative and metallic works for interior and exterior works and as primer on any wooden, mdf and metallic surface before applying final coat paint. The primer has high filling and covering power and is easily rasped and quick drying.

Instructions for use: Applied surfaces should be dry, clean and free from dust and oil. Should be thinned with "Linx Sellülozik Tiner" and applied with brush roller and pistol. Approximately after 16 hours final coat paint may be applied.

Consumption: 8-10 m²/L on a single coat subject to pores and absorption capacity of the surface.

Storage: Should be stored in closed containers between 5-35°C temperatures away from direct sunlight in a non-humid place. Storage period: 2 years.

Safety measures: R10: Is inflammable. R66: May cause skin dryness and cracks when repeatedly exposed to. R67: Vapors may cause lethargy and dizziness. S2: Keep out of the reach of children. S3/7/9: Store the package closed in a cool and well-aired place. S16: Keep the paint away from potential fire sources. Smoking nearby is strictly prohibited. S23: Do not inhale. S24/25: Avoid eye and skin contact. S26: After eye contact wash immediately with plenty of water. S29: Do not dispose to sewerage. S46: Immediately go to the doctor when ingested and submit the package or label. S51: It should be used in well-aired places.

- Owns AZS-034-98 Standard
- Owns ISO 9001:2008 document

Panda Boya: Binagadi Highway, 4th Madan str.276/1

Tel: (+994 12) 401 90 00, Fax: (+994 12) 401 90 01