

### **Sellülozik Vernik (Cellulosic Varnish)**

**Introduction:** Nitrocellulose-based quick-drying varnish.

**Characteristics:** In interior and exterior works: mdf, wood, parquet, furniture and decorative works and as frame and covering on any surface as final coat. Being scratch and shockproof, it gives transparent, matt, silk matt look. It emphasizes color and vividness.

**Instructions for use:** Applied surfaces should be dry, clean and free from dust and oil. Should be thinned with "Linx Sellülozik Tiner" (Cellulosic Thinner) and applied with brush, roller and pistol. There should be 30-40 minutes interval between the coats.

**Dry-out time:** Touch-dry: 30-35 minutes. Raising period: minimum 5 hours. (23°C, relative humidity)

**Consumption:** 7-8 m<sup>2</sup>/L on a single coat subject to pores of the surface.

**Storage:** Should be stored in closed containers between 5-35°C temperatures away from direct sunlight in a non-humid place. Storage period: 2 years.

**Safety measures:** R10: Is inflammable. R66: May cause skin dryness and cracks when repeatedly exposed to. R67: Vapors may cause lethargy and dizziness. S2: Keep out of the reach of children. S3/7/9: Store the package closed in a cool and well-aired place. S16: Keep the paint away from potential fire sources. Smoking nearby is strictly prohibited. S23: Do not inhale. S24/25: Avoid eye and skin contact. S26: After eye contact wash immediately with plenty of water. S29: Do not dispose to sewerage. S46: Immediately go to the doctor when ingested and submit the package or label. S51: It should be used in well-aired places.

- Owns AZS-034-98 Standard
- Owns ISO 9001:2008 document

**Panda Boya:** Binagadi Highway, 4<sup>th</sup> Madan str.276/1

Tel: (+994 12) 401 90 00, Fax: (+994 12) 401 90 01