

### **Linx Sellülozik Dolğu Vernik (Cellulosic Filler Varnish)**

**Introduction:** Nitrocellulose-based filler varnish for mdf, wood and parquet surfaces.

**Characteristics:** Filler varnish is applied on mdf, wood, parquet, as well as on any surfaces in furniture and decorative works as frame and covering prior to final coat. It has high filling power and is easily rasped.

**Instructions for use:** Applied surfaces should be dry, clean and free from dust and oil.

**Dry-out time:** Touch-dry: 30-35 minutes. Complete dry-out: 5 hours. (23°C, relative humidity)

**Consumption:** 6-7 m<sup>2</sup>/L in a single coat, subject to absorption capacity of the surface.

**Storage:** Should be stored in closed containers between 5-35°C temperatures away from direct sunlight in a non-humid place. Storage period: 2 years.

**Safety measures:** R10: Is inflammable. R66: May cause skin dryness and cracks during repeated exposures. R67: Vapors may cause lethargy and dizziness. S2: Keep out of the reach of children. S3/7/9: Store the package closed in a cool and well-aired place. S16: Keep the paint away from potential fire sources. Smoking nearby is strictly prohibited. S23: Do not inhale. S24/25: Avoid eye and skin contact. S26: After eye contact wash immediately with plenty of water. S29: Do not dispose to sewerage. S46: Immediately go to the doctor when ingested and submit the package or label. S51: It should be used in well-aired places.

- Owns AZS-034-98 Standard
- Owns ISO 9001:2008 document

**Panda Boya:** Binagadi Highway, 4<sup>th</sup> Madan str.276/1

Tel: (+994 12) 401 90 00, Fax: (+994 12) 401 90 01