



## PANDA VARNISH

**DESCRIPTION:** One-component glossy varnish for parquet, applied to all types of parquet, based on polyurethane.

**SPECIFICATIONS:** Being extremely firm and elastic varnish, very resistant to scratches and wear. Protects the surface from many abrasive materials, such as detergent, alcohol, oil, tea, fruit juice.

### Technical details:

Gloss: Glossy

Solid content % (by weight ):

55+2

Density ( g/cm<sup>3</sup> ,20°C):

0.92+0.02

Viscosity (DIN Cup 4, sec.,20°C)

: 90-140

**APPLICATION:** After priming with PANDA CELLULOSE FILLING VARNISH and sanding, the newly laid and drained parquet should be dust-free and polished. If the old parquet was polished with wax lacquer, it must be thoroughly polished, and primed with PANDA CELLULOSE FILLING VARNISH. After sanding and cleaning dust from primed surfaces, they must be polished. It is recommended to fill the gaps between the parquet with a grinding chip and a paste made of parquet varnish. It is applied in two or three layers. Depending on the air temperature, you should wait 6-12 hours between the application of the layers. Ready to use, if desired, can be thinned with PANDA SYNTHETIC SOLVENT.

**DRYING TIME:** Touch dry in 6 hours, complete drying is completed in 12 hours. Physical and chemical resistance is reached in a maximum of 7 days.

**COVERAGE AREA:** 15 m<sup>2</sup> /L when applied in a single layer.

**SHELF LIFE:** It can be stored in a closed container in a cool and dry place, protected from frost and direct sunlight . For safe storage of the paint remaining in the container after use, thinner should be added until the paint is completely covered, or the container should be closed tightly and turned 180 ° once or twice.

**SAFETY PRECAUTIONS:** R10 : Flammable. R20/21/22: Harmful in contact with skin and if inhaled or swallowed.

S2: Keep out of reach of children. S16: Keep away from sources of ignition. NO SMOKING  
S24/25: Avoid contact with eyes and skin. S46: If swallowed consult a doctor immediately;  
show the container or the label S51: Use only in well-ventilated areas.

**Panda Boya:** Binagadi Highway, 4th Madan str.276/1

Tel:(+994 12) 401 90 00, Fax:(+994 12) 448 16 19



## PANDA VARNISH

- Certified with AZS-034-98
- Certified with ISO 9001:2008

Edition: 00

Date: 20.09.2015



# PANDA VARNISH

**Panda Boya:** Binagadi Highway, 4th Madan str.276/1

Tel:(+994 12) 401 90 00, Fax:(+994 12) 448 16 19