



PANDA MATT SYNTHETIC PAINT

DESCRIPTION: Alkyd based matt topcoat paint

SPECIFICATIONS: Produced for interior and used as a high coverage, quick-dry, no brush marks, washable and durable paint on wooden metal and wall surfaces. Excellent levels of whiteness and coverage on applied surfaces. Suitable for scanning, non-drip and free of brush marks, provides easy application with a brush and roller.

Technical details :

Gloss (60 C) :Max 11

Solid content % (by weight) : 85 +2

Density (g/cm³ ,20°C) :1.78+0.05

Viscosity (KU,25°C) : 125+5

APPLICATION: Wooden surfaces must be sanded to remove the roughness or any previous paint before priming with Panda WOOD PRESERVATIVE or Panda Antirust paint. Metal surfaces must be cleaned to remove any dirt, rust or grease before priming with Panda Antirust. Two coats are applied with one-day break between coats.Can be thinned by 5-10% with Panda SENTETİK TİNER. Use between +5°C and +30°C for brush, roller or spray application. Clean the tools you use with Panda Sentetik Tiner immediately after application.

DRYING TIME: 20 °C touch dry in 1-2 hours, dust-free dry in 3-4 hours, hard dry in 12-15 hours.

COVERAGE AREA: 15 m² /L in one coat

SHELF LIFE: Can be stored unopened in cool, dry, frost and sunlight-free conditions. When remains, in order to keep it safely, thinner should be added until the paint is completely covered, or the container should be closed tightly and turned 180 ° once or twice.

SAFETY PRECAUTIONS: R10 : Flammable. R20/21/22: Harmful in contact with skin and if inhaled or swallowed.

S2: Keep out of reach of children. S16: Keep away from sources of ignition. NO SMOKING S24/25: Avoid contact with eyes and skin. S46: If swallowed consult a doctor immediately; show the container or the label S51: Use only in well-ventilated areas.

Panda Boya: Binagadi Highway, 4th Madan str.276/1

Tel:(+994 12) 401 90 00, Fax:(+994 12) 448 16 19



PANDA MATT SYNTHETIC PAINT

Certified with AZS-034-98

- Certified with ISO 9001:2008