



## PANDA GLOSS SYNTHETIC PAINT

**DESCRIPTION:** Alkyd based gloss topcoat paint

**SPECIFICATIONS:** Used on wooden, plaster and metal surfaces in interior and exterior places, and on water surfaces of land and sea vehicles. High durability against yellowing. Easily applied gloss synthetic paint with good levels of coverage, spreading and adhesion.

**Technical details :**

Colours: Look at the colour catalogue

Gloss (60°) :Min. 85

Solid content % (by weight ) : 65 +2

Density ( g/cm<sup>3</sup> ,20°C) :1.05+1.20

Viscosity ( KU,25°C) : 120+5

Flash point: > 38 °C

**APPLICATION:** Wooden surfaces must be sanded to remove the roughness or any previous paint before priming with colourless Panda WOOD PRESERVATIVE or Panda Antirust paint. Metal surfaces must be cleaned to remove any dirt, rust or grease before priming with Panda Antirust. Two coats are applied with one-day break between coats.Can be thinned by 5-10% with Panda SENTETİK TİNER. Use between +5°C and +30°C for brush, roller or spray application. Clean the tools you use with Panda Sentetik Tiner immediately after application.

**DRYING TIME:** Touch dry in about 1-2 hours; dust-free dry in 7-8 hours; hard dry in 24 hours.

**COVERAGE AREA:** 10-12 m<sup>2</sup> /L in one coat

**SHELF LIFE:** Can be stored unopened in cool, dry, frost and sunlight-free conditions. When remains, in order to keep it safely, thinner should be added until the paint is completely covered, or the container should be closed tightly and turned 180 ° once or twice.

**SAFETY PRECAUTIONS:** R10 : Flammable. R20/21/22: Harmful in contact with skin and if inhaled or swallowed.

S2: Keep out of reach of children. S16: Keep away from sources of ignition. NO SMOKING S24/25: Avoid contact with eyes and skin. S46: If swallowed consult a doctor immediately; show the container or the label S51: Use only in well-ventilated areas.

**Panda Boya:** Binagadi Highway, 4th Madan str.276/1

Tel:(+994 12) 401 90 00, Fax:(+994 12) 448 16 19



## PANDA GLOSS SYNTHETIC PAINT

Certified with AZS-034-98

- Certified with ISO 9001:2008