

## **PANEXTER AKRILIK ƏSASLI MƏCUN (ACRYLIC-BASED PUTTY)**

**Introduction:** Acrylic-based interior and exterior surface paste.

**Characteristics:** This paste is used for smoothing the paint to be painted and filling cracks. It easily dries and water-proof, resistant to atmospheric effects and doesn't prevent air-prevention of the surface.

**Instructions for use:** Initially applied surface should be cleaned from other items and old paint. Panexter should be applied on the surface with spatula. The first coat should be completely dry when the second coat is applied. After it easily dries, priming is done with Panda Primer or Panbinder. Then any interior and exterior paint may be applied on it. Panexter is sold ready for use. No thinning is needed.

Temperature on the Panexter-applied surface should be between 5-35°C.

**Dry-out period:** Panexter dries during an hour. Complete dry-out period is 24 hours.

**Consumption:** 0.5-1.5kg/m<sup>2</sup> subject to the applied surface.

**Storage period:** May be stored closed in its original container without opening the lid, away from direct sunlight for 2 years.

**Safety Measures:** Avoid eye contact and ingestion. Keep out of the reach of children.

**Panda Boya:** Binagadi Highway, 4<sup>th</sup> Madan str.276/1

Tel: (+994 12) 401 90 00, Fax: (+994 12) 448 16 19