Edition: 00

Date: 02.01.2013

PANPLASTİK SU ƏSASLI İÇ SƏTH BOYASI (WATER-BASED INTERIOR SURFACE PAINT)

Introduction: Acrylic-based, water-thinned, highly resistant decorative, matt paint.

Characteristics: PanPlastik paint is resistant, decorative exterior surface paint that doesn't crack and has high adhesion force on any surface. It doesn't leave traces of brush and paint roller or leak when applied. This is an ultra-high opacity matt.

Technical characteristics:

Color: See color catalogue.

Brightness: Matt

Dissolved matter, (mass) : 69-70%

Particular weight (g/cm^3, 20°C): 1.68-1.69

Viscosity (KU, 25°C): 119-121

pH (25°C): 8.0-9.0

Instructions for use: Applied surface should be cleaned from other items and old paint. When the surface is properly prepared for last coat painting: the paint will adhere stronger, be smooth and perfect, dry equally and last longer. Firstly cracks are filled with PANEXTER. 2-4 hours after PANBINDER or PANPRIMER is applied, the paint is thinned with 15% water and applied twice using paint roller or brush with at least an hour interruption. Temperature of the surface and environment should be between 5-30°C while applying.

Dry-out period: Primary dry-out – 1 hour, complete dry-out – 20 hours.

Consumption: 10-12 m^2/lt for single coat subject to absorption capacity of the surface.

Storage period: May be stored closed in its original container away from direct sunlight for 2 years, provided that freezing is avoided. For more information please refer to Technical Support Section.

Safety Measures: Avoid eye contact and ingestion. Keep out of the reach of children

Packing information: 2.5lt, 7.5 lt, 15 lt

- Owns AZS-034-98 Standard
- Owns ISO 9001:2008 document

Panda Boya: Binagadi Highway, 4th Madan str.276/1

Tel: (+994 12) 401 90 00, Fax: (+994 12) 448 16 19