



SILICONE SILK-MATT WATER-BASED PAINT PANSATEN

DESCRIPTION: Decorative silk-matt finish for interior based on acrylic water and acrylic copolymer, with the addition of silicone.

SPECIFICATIONS: Eco-friendly, washable, non-yellowing, dust-repellent and dirt-repellent paint for the interior on a silky matte texture, designed for interior decorations, with a high covering ability. Water-repellent and vapor-permeable feature of silicone and special resin in its structure increases the ability of the paint to bleach and prevents its swelling and spillage, especially in wet conditions.

Technical details:

Colour: See in colour catalog

Solid content % (by weight):

56+58

Density (g/cm³ ,20°C):

1.31+1.35

Viscosity (cPs,25°C): 9000-

11000

pH (25°C): 8.0-9.0

Gloss (85C, gloss): 28-40 (60C,

gloss): 5-10

APPLICATION: Surfaces treated with PanSATEN must be smooth, strong, dry and free of dust. During application, the ambient and surface temperatures should be between 5°C and 30°C. Dimples and cracks must be filled with Panexter Paste and primed with Panda binder or Panda Primer. On primed surfaces should be applied in two layers after 18-24 hours of waiting. You should wait at least 4 hours between the layers. It should be properly applied to surfaces much screening to obtain the best result in the case of roller application, it is necessary to apply the product without compression. (The scanning is when roller is used by pulling up and down in one direction).

Tools used: Apply by brush or satin roller.

Thinning / Mixing Ratio: Can be thinned by 10-15% with water.

DRYING TIME: Touch dry in 15 minutes, dust-free dry in 30 minutes, hard dry in 4 hours.

COVERAGE AREA: 15-18 m²/L when applied in a single layer (16 m²/kg).

Panda Boya: Binagadi Highway, 4th Madan str.276/1

Tel:(+994 12) 401 90 00, Fax:(+994 12) 448 16 19



SILICONE SILK-MATT WATER-BASED PAINT PANSATEN

SHELF LIFE: Store in closed containers at 5-35 ° C, in a place protected from direct sunlight. Keep away from frost.

SAFETY PRECAUTIONS: R10 : Flammable. S24/25: Avoid contact with eyes and skin. S46: If swallowed consult a doctor immediately; show the container or the label.

- Certified with AZS-034-98
- Certified with ISO 9001:2008