



## PANTAVAN WATER-BASED SAILING PAINT

**DESCRIPTION:** Matt ceiling paint for decorative purposes on the basis of water and acrylic copolymer binder.

**SPECIFICATIONS:** Matte ceiling paint with a high coating ability, odorless. It is applied to all kinds of surfaces from plaster, gypsum and lime.

### Technical details:

Colour: White

Gloss: Matt

Solid content % (by weight ):

68+72

Density ( g/cm<sup>3</sup>,20°C):1.78+1.83

Viscosity ( cPs,25°C) : 17000-

23000

pH (25°C): 8.0-9.0

**APPLICATION:** a) Surface preparation: Dirty, dusty, swollen and old painted surfaces should be thoroughly cleaned and primed in a single layer by thinning 1/7 with Panda binder or Panda Primer. Panda Primer is recommended for internally plastered, non-dusting mineral-based surfaces. During application, the ambient and surface temperatures should be between 5°C and 30°C. It is applied in two layers. You should wait 2-3 hours between the application of the layers.

**Tools used:** It is applied with a brush or roller.

**Thinning / Mixing Ratio:** Can be thinned by 15-20% with water.

**DRYING TIME:** It dries in 1-3 hours.

**COVERAGE AREA:** 8-10 m<sup>2</sup>/L when applied in a single layer (5-7 m<sup>2</sup>/kg).

**SHELF LIFE:** Store in closed containers at 5-35 ° C, in a place protected from direct sunlight. Keep container closed when not in use. Keep away from frost.

**SAFETY PRECAUTIONS:** S2: Keep out of reach of children. S24/25: Avoid contact with eyes and skin. S46: If swallowed consult a doctor immediately; show the container or the label.

- Certified with AZS-034-98
- Certified with ISO 9001:2008

**Panda Boya:** Binagadi Highway, 4th Madan str.276/1

Tel:(+994 12) 401 90 00, Fax:(+994 12) 448 16 19