

SUTUT SU ƏSASLI ÇÖL SƏTH BOYASI (WATER-BASED EXTERIOR SURFACE PAINT)

Introduction: Acrylic-based, water-thinned, elastic, moisture-resistant, anti-bacterial matt facade paint.

Characteristics: Sutut paint is decorative exterior surface paint that is resistant to water and atmospheric effects, is highly adherent on any surface, doesn't crack, creates elastic coating on the applied surface, doesn't leave traces of brush and paint roller and doesn't leak when applied. In addition to being ultra-high opacity matt, it also prevents mould growth and ensures removal of moisture on walls thanks to its air-penetrating feature.

Technical characteristics:

Color: See color catalogue.

Brightness: Matt

Dissolved matter, (mass) : 52-53%

Particular weight (g/cm³, 20°C): 1.28-1.29

Viscosity (KU, 25°C): 85-90

pH (25°C): 8.0-9.0

Instructions for use: Applied surface should be cleaned from other items and old paint. When the surface is properly prepared for last coat: the paint will adhere stronger, will be smooth and perfect, dry equally and last longer. Initially cracks are filled with PANEXTER. Then priming is carried out with PANDA PRIMER OR PANDABINDER, and 2-3 hours later paint is thinned with 15% water and applied crosswise twice using paint roller or brush with at least an hour interruption. Painted surface should not be exposed to frost and rain for 36 hours. Temperature of the surface and environment should be between 5-30°C while applying.

Dry-out period: dries between 1-3 hours. The second coat is applied after 3 hours. Full dry-out period is 24 hours.

Consumption: 11-13 m²/lt for single coat subject to absorption capacity of the surface.

Storage period: May be stored closed in its original container away from direct sunlight for 2 years, provided that freezing is avoided. For more information please refer to Technical Support Section.

Safety Measures: Avoid eye contact and ingestion. Keep out of the reach of children

Packaging information: 2.5lt, 7.5 lt, 15 lt

- Owns AZS-034-98 Standard
- Owns ISO 9001:2008 document

Panda Boya: Binagadi Highway, 4th Madan str.276/1

Tel: (+994 12) 401 90 00, Fax: (+994 12) 448 16 19